

2217Pwc

21,6" TFT MONITOR



Panel	21,6" (548mm) a-si TFT Active matrix LCD panel
Design Line	Profi
Pixel / Dot Pitch	0.277 mm X 0.277 mm
Viewable Image Size (Diagonal)	548mm
Display Area	464.94mmx290.58mm
Brightness	300 cd/m ²
Contrast Ratio	3000:1 (DCR)
Typ. Response Time (tr)	5ms
Viewing Angle	170/160 (CR≥10)
Compatibility	VGA, SVGA, XGA, VESA DPMS, VESA DDCB, SXGA, WXGA, WSXGA Mac Equipment: VGA, SVGA, XGA, SXGA
Scanning Frequency	Horizontal: 30kHz-83kHz Vertical: 55kHz - 75kHz
Pixel Frequency	165 MHz
Maximum Resolution	1680x1050@60Hz
Recommended Resolution	1680x1050@60Hz
Resolution Supported	from 640x480 up to 1680x1050/60Hz
Colours	16.7M
Signal Input	Analog RGB, DVI-D
Connectors	15-pin D-Sub & 24-pin DVI-D
Power Source	Power Input: 90~240VAC, 50/60Hz
Power Consumption	On: <49W , Stabdy: < 1 W
Plug & Play	DDC 1/2B/CI
EPA ENERGY STAR®	
User Control	Eco / up, Vol / down, MENU / Right, Auto /Left, Power on/off
Function	Brightness, Contrast, Focus, Clock, H/V Position, Colour Temp. (Warm, Cool & User) Input Select, OSD H/V, OSD Timeout, OSD Language, Input Signal Information, Reset, Exit
OSD Languages	new 8 languages
Speaker	1.5W x2 Mircophone x1
Emissions Standard	
Regulation	cUL, FCC, CE, EPA, CCC, TUV/S, Vista Premium
Other Features	1,3 Megapixel Webcam, USB (pull down x3 ,Spiral stand ; Navigation key, High glossy, 110 mm Height Adjustment, Mircophone x 1
Dimensions (WxHxD)	
Weight	505 X 442 X 280
Loading Qty w/pallet	Net: 5,58 kg Gross: 7,8 kg 20" container: 288 sets (w.pallet)
Warranty	40" container: 608 sets (w.pallet)
EAN Code	3 Years Parts & Labour

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.

SPECIFICATIONS

