

# 2217Pwc

## 21,6" TFT MONITOR



<b>Panel</b>	21,6" (548mm) a-si TFT Active matrix LCD panel
<b>Design Line</b>	<b>Profil</b>
<b>Pixel / Dot Pitch</b>	0.277 mm X 0.277 mm
<b>Viewable Image Size (Diagonal)</b>	548mm
<b>Display Area</b>	464.94mmx290.58mm
<b>Brightness</b>	300 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	3000:1 (DCR)
<b>Typ. Response Time (tr)</b>	5ms
<b>Viewing Angle</b>	170/160 (CR≥10)
<b>Compatibility</b>	VGA, SVGA, XGA, VESA DPMS, VESA DDCB, SXGA, WXGA, WSXGA Mac Equipment: VGA, SVGA, XGA, SXGA
<b>Scanning Frequency</b>	Horizontal: 30kHz-83kHz Vertical: 55kHz - 75kHz
<b>Pixel Frequency</b>	165 MHz
<b>Maximum Resolution</b>	1680x1050@60Hz
<b>Recommended Resolution</b>	1680x1050@60Hz
<b>Resolution Supported</b>	from 640x480 up to 1680x1050/60Hz
<b>Colours</b>	16.7M
<b>Signal Input</b>	Analog RGB, DVI-D
<b>Connectors</b>	15-pin D-Sub & 24-pin DVI-D
<b>Power Source</b>	Power Input: 90~240VAC, 50/60Hz
<b>Power Consumption</b>	On: <49W , Stabdy: < 1 W
<b>Plug &amp; Play</b>	DDC 1/2B/CI
<b>EPA ENERGY STAR®</b>	
<b>User Control</b>	Eco / up, Vol / down, MENU / Right, Auto /Left, Power on/off
<b>Function</b>	Brightness, Contrast, Focus, Clock, H/V Position, Colour Temp. (Warm, Cool & User) Input Select, OSD H/V, OSD Timeout, OSD Language, Input Signal Information, Reset, Exit
<b>OSD Languages</b>	new 8 languages
<b>Speaker</b>	1.5W x2 Mircophone x1
<b>Emissions Standard</b>	
<b>Regulation</b>	cUL, FCC, CE, EPA, CCC, TUV/S, Vista Premium
<b>Other Features</b>	1,3 Megapixel Webcam, USB (pull down x3 ,Spiral stand ; Navigation key, High glossy, 110 mm Height Adjustment, Mircophone x 1
<b>Dimensions (WxHxD)</b>	
<b>Weight</b>	505 X 442 X 280
<b>Loading Qty w/pallet</b>	Net: 5,58 kg Gross: 7,8 kg 20" container: 288 sets (w.pallet)
<b>Warranty</b>	40" container: 608 sets (w.pallet)
<b>EAN Code</b>	3 Years Parts & Labour

Note: Specifications are subject to change without notice. \*Wall mount arm & bracket not included.

## SPECIFICATIONS

