

I NEED SPECIFICATIONS



Panel	TFT Active Matrix LCD, Slim Cabinet VIS: 20" (50.8cm), Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Design
Pixel / Dot Pitch	0.255mm x 0.255mm
Viewable Image Size (Diagonal)	20"
Display Area	408mm x 306mm
Brightness	250 cd/m ² (typ)
Contrast Ratio	700:1 (typ)
Typ. Response Time (tr+tf)	16ms (grey to grey)
Viewing Angle	Horizontal: 170 Degrees Vertical: 170 Degrees
Compatibility	VESA, SXGA, XGA, SVGA, VGA Mac [®] Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~80KHz (analogue) Vertical: 55~75 Hz
Pixel Frequency	135 MHz
Maximum Resolution	1600x1200
Recommended Resolution	1600x1200@60Hz
Resolution Supported	800x600@60/75Hz, 1024x768@60/75Hz, 1280x1024@60/75Hz, 1600x1200@60Hz
Colours	16.7M
Signal Input	Analogue: Video: 0.7Vp-p, RGB analogue Separate Sync: TTL Level H/V Sync: Positive / Negative Digital Input: DVI-D (TMDS)
Connectors	Analogue RGB Signal: 15-pin D-sub Male (Attached) DVI-D: 24-pin DVI-D Power: 3-pin Plug (CEE22)
Power Source	Power Adapter Input: Universal 100~240VAC, 50/60Hz Power Adapter Output: 12VDC 6A (Max)
Power Consumption	60Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR[®]	Yes
User Control	Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key
Function	Brightness, Contrast, Input Select, Focus, Clock, H/V Position, Language, Recall, Exit, RGB
OSD Languages	English, German, French, Spanish, Italian
Emissions Standard	TCO 03
Regulations	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Pixel Fault Class II, Windows [®] XP Logo
Other Features	VESA 100mm Wall Mountable*, High Adjustment 80mm, Kensington Security Slot
Dimensions (WxHxD mm)	Monitor: 344-417x446x246 Carton: 225x516x425
Weight	Net: 7.5kgs Gross: 9.5kgs
Loading Qty w/pallet	20' = 550 pcs 40' = 1150 pcs
Warranty	3 Years Parts & Labour

Note: Specifications are subject to change without notice.

* Wall mount arm & bracket not included.