

I NEED SPECIFICATIONS



Panel	TFT Active Matrix LCD, Super Narrow Bezel VIS: 17" (43.2cm), Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Design
Pixel / Dot Pitch	0.264mm x 0.264mm
Viewable Image Size (Diagonal)	17"
Display Area	338mm x 270mm
Brightness	300 cd/m ² (typ)
Contrast Ratio	700:1 (typ)
Typ. Response Time (tr+tf)	8ms
Viewing Angle	Horizontal: 140 Degrees Vertical: 130 Degrees
Compatibility	VESA, SXGA, XGA, SVGA, VGA Mac [®] Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~80KHz (analogue) Vertical: 55~75 Hz
Pixel Frequency	135 MHz
Maximum Resolution	1280x1024@75Hz (Analogue) 1280x1024@75Hz (DVI-D)
Recommended Resolution	1280x1024@60Hz
Resolution Supported	640x350@70Hz, 720x400@70Hz, 640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
Colours	16.0M
Signal Input	Video: 0.7Vp-p, RGB analogue Separate Sync: TTL Level H/V Sync: Positive / Negative Digital Input: DVI-D (TMDS)
Connectors	RGB Signal: 15-pin D-sub Male (Attached) DVI-D: 24-pin DVI-D Power: 3-pin Plug (CEE22)
Power Source	Power Adapter Input: Universal 100~240VAC, 50/60Hz Power Adapter Output: 12VDC 5A (Max)
Power Consumption	45Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR[®]	Yes
User Control	Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key
Function	Brightness, Contrast, Focus, Clock, H/V Position, Auto-Center, Language, Recall, Exit, RGB
OSD Languages	English, German, French, Spanish, Italian
Emissions Standard	TC099
Regulations	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows [®] XP Logo
Other Features	VESA 100mm Wall Mountable*, High Adjustment 80mm, Kensington Security Slot
Dimensions (WxHxD mm)	Monitor: 303-383x367x246 Carton: 422x380x178
Weight	Net: 5.0kgs Gross: 6.5kgs
Loading Qty w/pallet	20' = 936 pcs 40' = 1872 pcs
Warranty	3 Years Parts & Labour

Note: Specifications are subject to change without notice.

* Wall mount arm & bracket not included.

** Available: Q2 / 2005