

# I NEED SPECIFICATIONS



<b>Panel</b>	TFT Active Matrix LCD, Slim Cabinet VIS: 17" (43.2cm), Diagonal Hard Coating (3H), Anti-glare Treatment
<b>Design Line</b>	<b>Basic</b>
<b>Pixel / Dot Pitch</b>	0.264mm x 0.264mm
<b>Viewable Image Size (Diagonal)</b>	17"
<b>Display Area</b>	338mm x 270mm
<b>Brightness</b>	300 cd/m <sup>2</sup> (typ)
<b>Contrast Ratio</b>	500:1
<b>Typ. Response Time (tr+tf)</b>	12ms
<b>Viewing Angle</b>	Horizontal: 140 Degrees Vertical: 130 Degrees
<b>Compatibility</b>	VESA, SXGA, XGA, SVGA, VGA Mac® Equipped With VGA Port
<b>Scanning Frequency</b>	Horizontal: 30K~80KHz Vertical: 55~75 Hz
<b>Pixel Frequency</b>	135 MHz
<b>Maximum Resolution</b>	1280x1024@75Hz
<b>Recommended Resolution</b>	1280x1024@60Hz
<b>Resolution Supported</b>	640x350@70Hz, 740x400@70Hz, 640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
<b>Colours</b>	26.2M
<b>Signal Input</b>	Video: 0.7Vp-p, RGB analogue Separate Sync: TTL Level H/V Sync: Positive / Negative
<b>Connectors</b>	RGB Signal: 15-pin D-sub Male (Attached) Power: 3-pin Plug (CEE22)
<b>Power Source</b>	Power Input: Universal 100~240VAC, 50/60Hz
<b>Power Consumption</b>	45Watts (Max)
<b>Plug &amp; Play</b>	DDC1/2B
<b>EPA ENERGY STAR ®</b>	Yes
<b>User Control</b>	Stand-by Power, Auto Config
<b>Function</b>	Brightness, Contrast, Focus, Clock, H/V Position, Language, Colour Temperature (C1, C2), Reset, Exit, RGB
<b>OSD Languages</b>	English, German, French, Spanish, Italian
<b>Speaker</b>	2 x 1.5Watt Volume, Earphone Output
<b>Emissions Standard</b>	TC003
<b>Regulations</b>	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows® XP Logo
<b>Other Features</b>	VESA 75mm Wall Mountable*, Kensington Security Slot
<b>Dimensions (WxHxD mm)</b>	Monitor: 380x86x385 mm Carton: 435x134x456 mm
<b>Weight</b>	Net: 4.0 Kg Gross: 5.0 Kg
<b>Loading Qty w/pallet</b>	40" 2052 pcs 20" 988 pcs
<b>Warranty</b>	3 Years Parts & Labour

**Note:** Specifications are subject to change without notice.

- \* Wall mount arm & bracket not included.
- \*\* Available: Q3/2005
- \*\*\* Available in RGB Analogue mode only.