

I NEED SPECIFICATIONS



Panel	TFT Active Matrix LCD, Super Narrow Bezel VIS: 19" (48.2cm), Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Design
Pixel / Dot Pitch	0.294mm x 0.294mm
Viewable Image Size (Diagonal)	19"
Display Area	376mm x 301mm
Brightness	250 cd/m ² (typ)
Contrast Ratio	550:1 (typ)
Typ. Response Time (tr+tf)	8ms
Viewing Angle	Horizontal: 140 Degrees Vertical: 130 Degrees
Compatibility	VESA, SXGA, XGA, SVGA, VGA Mac [®] Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~80KHz (analogue) Vertical: 55~75 Hz
Pixel Frequency	135 MHz
Maximum Resolution	1280x1024@75Hz (Analogue) 1280x1024@75Hz (DVI-D)
Recommended Resolution	1280x1024@60Hz
Resolution Supported	640x350@70Hz, 740x400@70Hz, 640x480@60/75Hz, 800x600@60/75Hz, 1024x768@60/70/75Hz, 1280x1024@60/75Hz
Colours	16.0M
Signal Input	Analogue: Video: 0.7Vp-p, RGB analogue Separate Sync: TTL Level H/V Sync: Positive / Negative Digital Input: DVI-D (TMDS)
Connectors	Analogue RGB Signal: 15-pin D-sub Male (Attached) DVI-D: 24-pin DVI-D Power: 3-pin Plug (CEE22)
Power Source	Power Adapter Input: Universal 100~240VAC, 50/60Hz Power Adapter Output: 12VDC 5A (Max)
Power Consumption	45Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR[®]	Yes
User Control	Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key
Function	Brightness, Contrast, Input Select, Focus, Clock, H/V Position, Language, Recall, Exit, RGB
OSD Languages	English, German, French, Spanish, Italian
Emissions Standard	TC099
Regulations	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows [®] XP Logo
Other Features	VESA 100mm Wall Mountable*, High Adjustment 80mm, Kensington Security Slot
Dimensions (WxHxD mm)	Monitor: 336-415x410x246 Carton: 482x424x175
Weight	Net: 6.0kgs Gross: 8.5kgs
Loading Qty w/pallet	
Warranty	3 Years Parts & Labour

Note: Specifications are subject to change without notice.

* Wall mount arm & bracket not included.

** Available: Q2 / 2005